

## Specifications



## Circuit Breaker Brame, UEM5-400(MCCB)

### Main

Range	UEM5
Product Name	UEM5
Device Short Name	UEM5-400
Product or Component Type	Circuit breaker
Device Application	Distribution
Poles Description	3P、 4P
Rated Current [In]	225 A at 40 °C
	250 A at 40 °C
	315 A at 40 °C
	350 A at 40 °C
	400 A at 40 °C
Rated Operational Voltage[Ue]	400 V AC
Network Type	AC
Network Frequency	50 Hz
Suitability for Isolation	Yes conforming to IEC 60947-2
Utilisation Category	Category A
Breaking Capacity	L、 M、 H
Rated Ultimate Short-Circuit Breaking Capacity [Icu]	L: 50 kA Icu at 400 V AC 50 Hz conforming to IEC 60947-2 M: 65 kA Icu at 400 V AC 50 Hz conforming to IEC 60947-2 H: 85 kA Icu at 400 V AC 50 Hz conforming to IEC 60947-2

Rated Service Short-Circuit Breaking Capacity[Ics]	L: 35 kA Ics at 400V AC 50Hz conforming to IEC 60947-2 M: 50 kA Ics at 400 V AC 50 Hz conforming to IEC 60947-2 H: 65 kA Ics at 400 V AC 50 Hz conforming to IEC 60947-2
--	--

Arcing Distance (mm)	≤50mm
Trip Unit Technology	Thermal-magnetic Magnetic
Control Type	Operated by handle Operated by motorized operating mechanism Operated by rotary operating mechanism
Circuit Breaker Mounting Mode	Fixed Plug-in type Withdrawable type

## Complementary

Rated Insulation Voltage [Ui]	800 V AC 50 Hz
Rated Impulse Withstand Voltage [Uimp]	8 kV
Mechanical Durability	4000 cycles
Electrical Durability	1000 cycles at 400 V In
Mounting Position	Horizontal and vertical flat on the back
Connection Pitch	44 mm
Instantaneous Protection	10In (For power distribution)
Pick-up Adjustment Range [Ii]	12In (For motor protection)
Electrical Accessory Types	Alarm contact Shunt release Auxiliary contact Undervoltage release
Width	140mm (3P) 、184mm (4P)
Height	257 mm
Depth	97 mm
Net Weight	6.2kg (3P) /8.0 kg (4P)

## Environment

Standards	EN/IEC 60947-2
Product Certifications	CCC CB

Pollution Degree	3 conforming to IEC 60664-1
Ambient Air Temperature for Operation	-25...70 °C
Ambient Air Temperature for Storage	-40...70 °C
Relative Humidity	0...95 % (25°C)
Operating Altitude	0...2000 m without derating 2000 m...4000 m with derating

## Packing Units

Package	3P	4P
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package Height 1	18.5cm	18.5cm
Package Width 1	22cm	26.5cm
Package Length 1	37.8cm	37.8cm
Package Weight 1	6.86kg	8.76kg
Unit Type of Package 2	Box	
Number of Units in Package 2	2	2
Package Height 2	19.5cm	19.5cm
Package Width 2	38.5cm	38.5cm
Package Length 2	45.5cm	54.5cm
Package Weight 2	13.72kg	17.52kg

## Offer Sustainability

China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
-----------------------	--