

## Specifications



## Circuit Breaker Frame, UEM5Z1-400(MCCB)

### Main

Range	UEM5Z1
Product Name	UEM5Z1
Device Short Name	UEM5Z1-400
Product or Component Type	Circuit breaker
Device Application	Distribution
Poles Description	3P、 4P
Rated Current [In]	400 A at 40 °C
Rated Operational Voltage[Ue]	400 V AC 50 Hz
Network Type	AC
Network Frequency	50 Hz
Suitability for Isolation	Yes conforming to EN/IEC 60947-2
Utilisation Category	Category B
Breaking Capacity	M、 H
Rated Ultimate Short-Circuit Breaking Capacity [Icu]	M: 65 kA Icu at 400 V AC 50 Hz conforming to IEC 60947-2 H: 85 kA Icu at 400 V AC 50 Hz conforming to IEC 60947-2
Rated Service Short-Circuit Breaking Capacity[Ics]	M: 50 kA Ics at 400 V AC 50 Hz conforming to IEC 60947-2 H: 65 kA Ics at 400 V AC 50 Hz conforming to IEC 60947-2
Arcing Distance (mm)	≤50mm
Trip Unit Technology	Thermal-magnetic
Trip Unit Protection Functions	LSIP (overload long time delay + short circuit short time delay + short circuit instantaneous + pre-alarm protection)
Control Type	Operated by handle Operated by motorized operating mechanism

Operated by rotary operating mechanism

Circuit Breaker Mounting Mode	Fixed Plug-in type Withdrawable type
-------------------------------	--

## Complementary

Rated Insulation Voltage [Ui]	800 V AC 50Hz
Rated Impulse Withstand Voltage [Uimp]	8 kV
Mechanical Durability	4000 cycles
Electrical Durability	1000 cycles at 400 V In
Mounting Position	Horizontal and vertical flat on the back
Connection Pitch	44 mm
Long-Time Pick-up Adjustment Type Ir (thermal protection)	Adjustable
Long-Time Protection Pick-up Adjustment Range [Ir]	200A, 225A, 250A, 275A, 300A, 315A, 350A, 375A, 400A
Long-Time Protection Delay Adjustment Type tr	Adjustable
Long-Time Protection Delay Adjustment Range [tr]	12s, 60s, 80s, 100s, OFF
Instantaneous Protection Pickup Adjustment Type li	Adjustable
Instantaneous Protection Pick-up Adjustment Range [li]	(3, 4, 5, 6, 7, 8, 9, 10, 12) xIn, OFF
Short-Time Protection Pick-up Adjustment Type Isd	Adjustable
Short-Time Protection Pick-up Adjustment Range[Isd]	(2, 3, 4, 5, 6, 7, 8, 9, 10, 12) xIr, OFF
Short-Time Protection Delay Adjustment Type tsd	Adjustable
Short-Time Protection Delay Adjustment Range [tsd]	0.06s, 0.1s, 0.2s, 0.3s
Pre-alarm Protection Pick-up Adjustment Range [Ip]	(0.7, 0.8, 0.9, 1.0)xIr
Electrical Accessory Types	Alarm contact Shunt release Auxiliary contact

	Undervoltage release
Width	140mm (3P) 、 184mm (4P)
Height	257 mm
Depth	97 mm
Net Weight	5.7kg (3P) /7.5 kg (4P)

## Environment

Standards	EN/IEC 60947-2
Product Certifications	CCC CB
Pollution Degree	3 conforming to IEC 60664-1
Ambient Air Temperature for Operation	-25...70 °C
Ambient Air Temperature for Storage	-40...70 °C
Relative Humidity	0...95 % (25°C)
Operating Altitude	0...2000 m without derating 2000 m...4000 m with derating

## Packing Units

Package	3P	4P
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package Height 1	18.5cm	18.5cm
Package Width 1	22cm	26.5cm
Package Length 1	37.8cm	37.8cm
Package Weight 1	6.36kg	8.26kg
Unit Type of Package 2	Box	
Number of Units in Package 2	2	2
Package Height 2	19.5cm	19.5cm
Package Width 2	38.5cm	38.5cm
Package Length 2	45.5cm	54.5cm
Package Weight 2	16kg	20.5kg

## Offer Sustainability

China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
-----------------------	---