

Specifications



Contactors For Capacitor Switching, UEC1-WK

Main

Product Series	UEC1
Product or Component Type	Contactors for capacitor switching
Device Short Name	UEC1-WK
Contactor Application	Power-factor correction
Control Circuit Type	AC
Coil Type	AC 50/60 Hz
Poles Description	3P
Pole Contact Composition	3 NO
Auxiliary Contact Type	1NO+2NC, 2NO+3NC
[Us]Control Circuit Voltage (AC 50/60Hz)	Voltage (V) : 24 36 42 48 110 115 127 220 230 240 380 400 415 Code: B7 CC7 D7 E7 F7 FE7 FC7 M7 P7 U7 Q7 V7 N7
Imaginary Power	35 kvar at 220...230 V 50/60 Hz (≤ 60 °C) 65 kvar at 400...440 V 50/60 Hz (≤ 60 °C) 104 kvar at 660...690 V 50/60 Hz (≤ 60 °C)

Complementary

Mounting Support	Screw ; 35mm or 75mm DIN Rail
Tightening Torque	Power circuit: 80 lb.in (9 N·m) -on bolt clamp terminals - with internal hexagon socket wrench 4 mm Control circuit: 11 lb.in (1.2 N·m) -on screw clamp terminals - with screwdriver flat \varnothing 6 mm Control circuit: 11 lb.in (1.2 N·m) -on screw clamp terminals -with screwdriver Philips No 2

[Ue]Rated Operational Voltage	Power circuit: ≤ 690 V AC 50/60Hz
Minimum Switching Voltage	24 V for signalling circuit
Minimum Switching Current	0.1A for signalling circuit
Height	161 mm
Width	70 mm
Depth	172.5 mm
Net Weight	1.45 kg

Environment

Standards	GB / T 14048.4, GB / T 14048.5, IEC/EN 60947-4-1, IEC/EN 60947-5-1
Product Certifications	CCC, CE
IP Degree of Protection	IP20 front face conforming to IEC 60529
Ambient Air Temperature For Operation	-25...60 °C
Ambient Air Temperature For Storage	-60...80 °C
Operating Altitude	0...3000 m without derating

Packing Units

Unit Type of Package 1	1 box
Number of Units in Package 1	1 pcs
Package 1 Height	18.5 cm
Package 1 Width	8.1 cm
Package 1 Length	16.8 cm
Package 1 Weight	1.50 kg
Unit type of Package 2	1 carton
Number of Units in Package 2	10 pcs
Package 2 Height	22.5 cm
Package 2 Width	37.5 cm
Package 2 Length	46.0 cm
Package 2 Weight	16.3 kg

Offer Sustainability

REACH Regulation	Conforming
------------------	------------

EU RoHS Directive	Conforming
-------------------	------------

Mercury Free	Yes
--------------	-----

China RoHS Regulation	Conforming
-----------------------	------------


Products Outside China RoHS Control	Yes
-------------------------------------	-----

RoHS Exemption Information	Yes
----------------------------	-----

Contractual warranty

Warranty	18 months
----------	-----------

Dimensions



Note: The unit is mm. The tolerance for mounting holes: ± 0.5 ; for other external dimensions: ± 1.5 , unless otherwise specified.