

Specifications



Auxiliary Contact

Main

Range	UEB3/UEB6
Product Name	Auxiliary contact
Device Short Name	B3AUX
Product or Component Type	Auxiliary contact
Device Application	Provide Auxiliary Signals
Contact Composition	1NC+1NO
Rated current	AC13: $I_e=3A$; $U_e=250V$ AC15: $I_e=2A$; $U_e=250V$ DC12: $I_e=0.5A$; $U_e=110V$

Complementary

Range Compatibility	UEB3-63、UEB3-40、UEB6-63、UEB6-40
Rated Insulation voltage	500V
Rated Impulse Withstand Voltage	4kV
Local Signal Indication	Mechanical indicator window
Installation Type	Snap Lock
Mounting Method	DIN Rail Installation
Width	8.9mm
Wiring Capability	$1 \times 0.5 \text{ mm}^2 \dots 1 \times 2.5 \text{ mm}^2$
Strip Length	8mm
Tightening Torque	0.6 N·m

Environment

Standards	GB/T 14048.5; EN60947-5-1; BS EN 60947-5-1
-----------	--

IP Degree of Protection	IP20
-------------------------	------

Ambient Air Temperature for Operation	-35...70 °C
---------------------------------------	-------------

Ambient Air Temperature for Storage	-40...85 °C
-------------------------------------	-------------

Contractual warranty

Warranty	18 months
----------	-----------