


HFA6

FORCE-GUIDED RELAY


 File No.:E134517



File No.:B 053286 0043



Features

- Multi contact arrangements: 5NO+1NC, 4NO+2NC, 3NO+3NC
- Forcibly guided contacts according to IEC 61810-3
- 6A switching capability
- Low input power: 500mW
- High insulation capability: 10kV surge voltage between input and output
- UL insulation system: Class F available

RoHS compliant

CONTACT DATA

Contact arrangement	5NO+1NC (5H1D type) 4NO+2NC (4H2D type) 3NO+3NC (3H3D type)
Forcibly guided contacts Type(according to IEC61810-3)	Type A
Contact resistance ¹⁾	100mΩ (at 1A 6VDC)
Contact material	AgSnO ₂
Contact rating (Res. load)	6A 250VAC / 30VDC
Min.contact load ²⁾	5VDC 10mA
Max. switching voltage	400VAC / 30VDC
Max. switching current	6A
Max. switching power	1500VA / 180W
Mechanical endurance ³⁾	1 x 10 ⁷ OPS
Electrical endurance	1 x 10 ⁵ OPS (1NO: 6A 30VDC, Resistive load, Room temp., 1s on 9s off) 1 x 10 ⁵ OPS (1NO: 6A 250VAC, Resistive load, Room temp., 1s on 9s off)

- Notes:** 1) The data shown above are initial values.
 2) Min. contact load is just a reference value in normal temperature, normal humidity, normal pressure environment and with relay pin up, which will vary depending on the power-on and off frequency, environmental conditions, expected lifespan, and installation direction. Thus, please have confirmation tests with actual load before use. And it is recommended to avoid using the relay when the temperature is below 0°C.
 3) No loading test, no mechanical damage after the test.

COIL DATA at 23°C

Nominal Voltage VDC	Pick-up Voltage VDC max. ¹⁾	Drop-out Voltage VDC min. ¹⁾	Max. Voltage VDC ²⁾	Coil resistance Ω
5	3.8	0.5	5.5	50 x (1±10%)
6	4.5	0.6	6.6	72 x (1±10%)
9	6.8	0.9	9.9	162 x (1±10%)
12	9.0	1.2	13.2	288 x (1±10%)
18	13.5	1.8	21.78	648 x (1±10%)
24	18.0	2.4	26.4	1152 x (1±10%)
36	27.0	3.6	39.6	2592 x (1±10%)
48	36.0	4.8	52.8	4608 x (1±10%)
110	82.5	11	121	24200 x (1±10%)

- Notes:** 1) The data shown above are initial values.
 2) Maximum voltage refers to the maximum voltage which relay coil could endure in a short period of time.

CHARACTERISTICS

Insulation resistance	1000MΩ (at 500VDC)	
Dielectric strength	Between coil & contacts	4000VAC 1 min
	Between open contacts	1500VAC 1 min
Surge voltage	Between coil & contacts	2500VAC 1 min (11-12/13-14) 4000VAC 1 min (Other)
	Between contact sets	10kV (1.2 / 50μs) 5kV (1.2 / 50μs)
Operate time (at rated voltage)	20ms max.	
Release time (at rated voltage)	20ms max.	
Temperature rise (at rated voltage)	≤70K (Coil driving voltage: 1.1 times Un, Contact current -carrying: rated current, at 85 °C)	
Vibration resistance	NO/NC:10Hz to 55Hz 1.5mm DA NO:55Hz to 200Hz, 98m/s ² NC:55Hz to 200Hz, 49m/s ²	
Shock resistance	Functional	100m/s ²
	Destructive	980m/s ²
Creepage distance	Between coil & contacts	8mm
	Between contacts	5.5mm
Clearance distance	Between coil & contacts	8mm
	Between contacts	5.5mm
Humidity	5% to 85% RH	
Ambient temperature	-40°C to 85°C	
Termination	PCB	
Unit weight	Approx. 23g	
Construction	Flux proofed	

- Notes:** 1) The data shown above are initial values.
 2) UL insulation system: Class F, Class B.

COIL

Coil power Approx. 500mW

SAFETY APPROVAL RATINGS

UL/CUL	6A 277VAC / 250VAC / 125VAC at 85°C 6A 30VDC at 85°C Pilot duty: 1.5A 240VAC 3A 120VAC
TÜV	6A 277VAC / 30VDC 1.5A /2A 240VAC(AC-15)

- Notes:** 1) All values unspecified are at room temperature.
 2) Only typical loads are listed above. Other load specifications can be available upon request.



HONGFA RELAY

ISO9001, IATF16949, ISO14001, ISO45001, IECQ QC 080000, ISO/IEC 27001 CERTIFIED

2025 Rev. 1.00

ORDERING INFORMATION

Type	HFA6 / 24	-5H1D	T	G	F	(XXX)
Coil voltage	5,6, 9, 12, 18, 24, 36, 48,110VDC					
Contact arrangement	5H1D: 5NO+1NC 3H3D: 3NO+3NC		4H2D: 4NO+2NC			
Contact material	T: AgSnO ₂					
Contact plating	G: Gold plated					
Insulation class	F: Class F					
Special code ⁴⁾	XXX: Customer special requirement		Nil: Standard			


- Notes:**
- 1) Flux-proofed relays can not be used in the environment with pollutants like H₂S, SO₂, NO₂, dust, etc.
 - 2) Contact is recommended for suitable condition and specifications if water cleaning or surface process is involved in assembling relays on PCB.
 - 3) Avoid contamination with organic solvents for the case using PC materials, otherwise chemical reactions may occur which may cause the shell to swell or crack.
 - 4) The customer special requirement express as special code after evaluating by Hongfa.

OUTLINE DIMENSIONS, WIRING DIAGRAM AND PC BOARD LAYOUT

Unit: mm

HFA6/□□-5H1DT□ (□□□)


Outline Dimensions



P↑


Wiring Diagram

(Bottom view)



PCB Layout

(Bottom view)




OUTLINE DIMENSIONS, WIRING DIAGRAM AND PC BOARD LAYOUT

Unit: mm


HFA6/□□-4H2DT□ (□□□)

Outline Dimensions




Wiring Diagram

(Bottom view)




PCB Layout

(Bottom view)




HFA6/□□-3H3DT□ (□□□)

Outline Dimensions




Wiring Diagram

(Bottom view)



PCB Layout

(Bottom view)




Remark: 1) In case of no tolerance shown in outline dimension: outline dimension $\leq 1\text{mm}$, tolerance should be $\pm 0.2\text{mm}$; outline dimension $> 1\text{mm}$ and $\leq 5\text{mm}$, tolerance should be $\pm 0.3\text{mm}$; outline dimension $> 5\text{mm}$, tolerance should be $\pm 0.4\text{mm}$.


2) The tolerance without indicating for PCB layout is always $\pm 0.1\text{mm}$.

CHARACTERISTIC CURVES

MAXIMUM SWITCHING POWER




ENDURANCE CURVE




Test conditions:
1NO, Resistive load, 250VAC,
Room temp., 1s on 9s off
The data shown above are typical values.

COIL TEMPERATURE RISE



INDUCTIVE DURABILITY CURVE



Test conditions:
Connected to IEC61810-1 Appendix B Table
B.3 method test, at room temperature, 1NO,
1s on and 9s off.

Disclaimer

The specification is for reference only. See to "Terminology and Guidelines" for more information. Specifications subject to change without notice. We could not evaluate all the performance and all the parameters for every possible application. Thus the user should be in a right position to choose the suitable product for their own application. If there is any query, please contact Hongfa for the technical service. However, it is the user's responsibility to determine which product should be used only.

© Xiamen Hongfa Electroacoustic Co., Ltd. All rights of Hongfa are reserved.