

HFLPR4 plug series

POWER CONNECTOR



Features

- The contact are made of copper alloys with high conductivity
- It has the characteristics of reliable connection, soft insertion, low contact resistance and high current carrying density
- The use of crown springs for contact ensures contact reliability
- It is used for DC and AC input/output of power supplies module of UPS and servers
- Mating With: HFLPR4-ZS0711VYY Power connector socket

RoHS compliant

ELECTRICAL DATA

Rated Voltage		250VAC
Rated current	Ø1.02 Pin	5A
	Ø2.38 Pin	35A
Voltage Proof	Between Ø2.38 Pin	2500VAC
	Between Ø1.02 Pin	1000VAC
	Between Ø1.02 Pin and Ø2.38 Pin	2500VAC
Contact Resistance	Ø1.02 Pin	5.0mΩ Max
	Ø2.38 Pin	1.0mΩ Max
Insulation Resistance		1000MΩ Min

Notes: 1) The data shown above are initial values.

STORAGE REQUIREMENT

Environment temperature	-10°C to +40°C
Humidity	80% Max
Ambient gas	no acidity, no alkalescence and other corrosive gas
Stockpile period	Doesn't exceed one year from production date

Notes: 1) The data shown above are initial values.

CHARACTERISTICS

Temperature Range	-55°C to 125°C
Voltage surge	/
Salt Mist	48h
Humidity Temperature	40°C, 90% to 95%RH, 96h; No damage to parts ⁽²⁾
Temperature life	432 hours at 125°C ⁽²⁾
Thermal Shock	-55°C(30 min), +125°C(30 min), 15°C/min, 100 times ⁽³⁾
Mechanical Shock	Acceleration of 30g, half sine wave, lasting 11 ms,±X,±Y,±Z direction 3 times each, the current instantaneous break time is less than 1μs ⁽²⁾
Vibration	Frequency 10Hz~ 55Hz~ 10Hz,displacement amplitude 0.75mm, 55Hz~500Hz~55Hz, acceleration 10g, each vertical direction lasts for 2 hours, the current instantaneous break time is less than 1μs ⁽²⁾
Protection Grade	/
Quality	Approx.42.2g
Marking Mode	Laser etching
Durability	500 Times Min
Termination	PCB

Notes: 1) The data shown above are initial values.

- 2) The parts should not be damaged, and the contact resistance should meet the requirements of electrical performance parameters.
3) Meet the parts without damage, withstand voltage meet the requirements of electrical performance parameters.

ORDERING INFORMATION

Type	HFLPR4- T P 07 11 R B B
Type of Connector	T: Plug
Type of Contact	P: Contact pin
No.of Power Contact	07: 7 Power Contacts
No.of Signal Contact	11: 11 Signal Contacts
Structural Form	R: Right angle
Power pin wiring method	B: Welding
Signal pin wiring method	B: Welding




HONGFA POWER CONNECTOR SOCKET

2024 Rev. 1.00


OUTLINE DIMENSIONS AND PC BOARD LAYOUT

Unit: mm

Outline Dimensions



PCB Layout (Bottom view)



SELECTION OF PARTS

Serial No.	Part And Components Name	Material	Finishing
1	Mounting Plate	PBT	/
2	Cover Plate	PBT	/
3	Positioning plate	PBT	/
4	Ø1.02 Pin I	Brass	Gold plated
5	Ø2.38 Pin II	Brass	Gold plated
6	Ø2.38 Pin	Brass	Silver plated
7	12# Claw	Copper Alloy	Cu/Ct-P
8	20# Claw	Copper Alloy	Cu/Ct-P

Disclaimer

The specification is for reference only. See to "Terminology and Guidelines" for more information. Specifications subject to change without notice. We could not evaluate all the performance and all the parameters for every possible application. Thus the user should be in a right position to choose the suitable product for their own application. If there is any query, please contact Hongfa for the technical service. However, it is the user's responsibility to determine which product should be used only.

© Xiamen Hongfa Electroacoustic Co., Ltd. All rights of Hongfa are reserved.