

HFLPR14 socket series

POWER CONNECTOR



Features

- The socket contact uses red copper with coiled spring structure, integrating high current-carrying capacity and spring elasticity for greatly improved current rating
- Features reliable connection, smooth mating, low contact resistance and high current density.
- Suitable for charging piles, UPS, power supplies and control signals
- Mating With:
HFLPR14-TP0408RBB Power connector plug

RoHS compliant

ELECTRICAL DATA

Rated Voltage	1000V
Rated current	150A
Voltage Proof	3000VAC
Contact Resistance	≤0.4mΩ
Insulation Resistance	≥3000MΩ

Notes: 1) The data shown above are initial values.

STORAGE REQUIREMENT

Environment temperature	-10°C to +40°C
Humidity	80% Max
Ambient gas	No acidity, No alkalescence and other corrosive gas
Stockpile period	Doesn't exceed one year from production date

Notes: 1) The data shown above are initial values.

CHARACTERISTICS

Temperature Range	-40°C to 125°C
Salt Mist	48h
Damp heat, cyclic	25°C to 55°C, Relative humidity ≥95%RH, 6 cycles ⁽³⁾
Temperature life	168 hours at 125±2°C ⁽³⁾
Thermal Shock	-40°C(30 min), +125°C(30 min), 5 times ⁽³⁾
Mechanical Shock	Acceleration of 30m/s ² , half sine wave, lasting 11ms, ±X, ±Y, ±Z direction 3 times each, the current instantaneous break time is less than 1μs
Vibration	Frequency 10Hz ~ 55Hz ~ 10Hz, AM 0.75mm, each vertical direction lasts for 2h, the current instantaneous break time is less than 1μs
Protection Grade	IP20
Quality	Approx. 108.8g
Marking Mode	Laser etching
Durability	500 Times Min
Termination	PCB

Notes: 1) The data shown above are initial values.

- 2) The parts should not be damaged, and the contact resistance should meet the requirements of electrical performance parameters.
- 3) No physical damage, electrical and mechanical properties meet sequential testing.

ORDERING INFORMATION

	HFLPR14	-Z	S	04	08	V	Y	B
Type								
Type of Connector	Z: Socket							
Type of Contact	S: Female							
No. of Power Contact	04: 4 Power Contacts							
No. of Signal Contact	08: 4 Signal Contacts							
Structural Form	V: Vertical							
Power pin wiring method	Y: Crimping cables							
Signal pin wiring method	B: Welding							




HONGFA POWER CONNECTOR SOCKET

2026 Rev. 1.00


OUTLINE DIMENSIONS AND PC BOARD LAYOUT

Unit: mm

Outline Dimensions




PCB Layout
(Bottom view)



DIMENSION OF RELATED ACCESSORY(Package delivery)

Unit: mm

Ø8 Female



Assembly screw M4



SELECTION OF PARTS

Serial No.	Part And Components Name	Material	Finishing
1	Ø8 Female	Copper Alloy	Silver plated
2	Assembly screw M4	35#	Zinc plated



PRECAUTIONS FOR USE

1. Adapter cable:


Ø8 power contact: 35mm² / 2AWG.

2. The operation process is as follows:

Connect the AC input cable (crimp) ❖❖❖



Power cord production ❖❖❖



Disclaimer

The specification is for reference only. Specifications subject to change without notice.

We could not evaluate all the performance and all the parameters for every possible application. Thus the user should be in a right position to choose the suitable product for their own application. If there is any query, please contact Hongfa for the technical service. However, it is the user's responsibility to determine which product should be used only.

© Xiamen Hongfa Electroacoustic Co., Ltd. All rights of Hongfa are reserved.